

02292013 A



(19)

02292013 A

(11) Publication number:

Generated Document.

PATENT ABSTRACTS OF JAPAN

(51) Int. Cl.: B29C 45/26 B29C 33/38 B29C 45/72

(21) Application number: 01111772

(22) Application date: 29.04.89

(30) Priority:

(43) Date of application
publication: 03.12.90(84) Designated contracting
states:(71) Applicant: SOGO SHIKA IRYO
KENKYUSHO:KK(72) Inventor: MASUHARA HIDEKAZU
KOMIYA SHIGEO

(74) Representative:

(54) INJECTION MOLDING
METHOD OF
PHOTOPOLYMERIZATION
RESIN AND INJECTION
MOLDING APPARATUS
THEREOF

(57) Abstract:


PURPOSE: To manufacture
efficiently a resin molding having
excellent dimensional accuracy or
mechanical strength by press-casting
photopolymerization resin into
cavities formed in a male and female
mold made up of a transparent

02292013 A

material, and introducing and irradiating photopolymerization irradiating light into the cavity from the outside.

CONSTITUTION: Photosetting resin 6 is inputted into a photosetting resin kneading supplier 7, and then press-casted into a cavity 5 formed in a fixed side molding mole 4a and movable side transparent molding mold 4b through a cylinder 1 and nozzle 3 by means of a screw 2. Next, visible light produced by halogen lamps is irradiated to the photopolymerization resin 6 within the cavity 5 through a reinforced glass 4c and movable transparent molding mold 4b, and the movable side molding mold 4b is withdrawn for opening the molding mold, and thus a polymerized and cured photosetting resin molding is taken out thereof. By employing photopolymerization resin, a molding can be obtained, which can be injection-molded at low temperature and has excellent dimensional accuracy. And, since a heater in the screw and a cooling pipe in the mold are not required, the structure of the molding apparatus can be simple and small in size.

COPYRIGHT: (C)1990,JPO&Japio



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.